



GENERAL INFO

MAXIPLUS™ BAG FILTER HOUSING

The Puretec MaxiPlus[™] bag filter housing assembly is commonly used in high sediment, chemical and process applications where longer service life is required.

Durable and lightweight polypropylene construction is used giving a compact assembly.

The Puretec MPB Series is capable of flow rates of up to 180 litres per minute, 38°C temperature, and a maximum pressure of 520 kPa.

Available in 1½" connection size. The Bag filters come to suit in 1, 5, 10, 25, 50, 100 and 200 micron grades. Duplex systems, manifolded together are recommended for higher and/or uninterrupted flows. Custom design manifolds can be designed and supplied.

HOUSING SPECIFICATIONS AND PERFORMANCE DATA							
Product Code	Material of construction	Filter elements	Inlet/outlet Size	Gauge Size	O-ring option	Max. Flow	
MPB202B	Polypropylene	MPBR Series Polypropylene media	1½"	¼" NPTF	B-Buna	180 Lpm	
Bag Filter Replacements		Size (inches)	Description	Description		Flow Rate (Lpm)	
MPBR012		20"	1 micron rating		135		
MPBR052		20"	5 micron rating		140		
MPBR102		20"	10 micron rating		145		
MPBR252		20"	25 micron rating		158		
MPBR502		20"	50 micron rating		165		
MPBR1002		20"	100 micron rating		170		
MPBR2002		20"	200 micron rating		180		

For more information contact your local stockist or visit us at **puretecgroup.com** Australia **1300 140 140** | New Zealand **0800 130 140**



FEATURES & BENEFITS

- High capacity housings for flow rates up to 180 litres per minute
- Suitable for high flow applications
- Robust design for longevity and reliability
- Tough polypropylene construction
- Compact and economical, ideal for duplex systems
- Connection size 1½"

MATERIALS OF CONSTRUCTION

- Housing
- Cap

Polypropylene

Polypropylene

Polypropylene

Bismuth Brass (lead free)

High Density Polypropylene

- Gauge
- Vent Plug
- Drain Plug
- Ball Valve
- Basket


PVC/Buna-N Seals Polypropylene

Buna-N

38°C

- O-Ring and Gaskets
- Maximum Temperature

PERFORMANCE DATA



STANDARD INCLUSIONS

- 1x High Quality PP filter housing with drain port and ball valve
- 1x Polypropylene filter basket
- 1x pressure gauge
- 1x mounting bracket
- 1x spanner wrench

APPLICATIONS

- Desalination Prefiltration
- Waste water treatment
- Reverse Osmosis prefiltration
- Electronics chemical process
- Fine chemical process
 Before use, please refer to published reference materials for chemical.

SPARE PARTS

Ordering Code	Description
MPBOR	0-ring, suits MPB202 housing
\bigcirc	

MPBOR