



## RX Compression Fittings

- Body - Polypropylene
- Locking ring and Sleeve - Acetyl
- Sealing ring - Nitrile rubber seal
- 15mm-50mm suitable for **HIGH Density Pipe** manufactured to RX Standard or NZS Standard and **MEDIUM Density MDID** to RX Standard
- 15mm-40mm suitable for **LOW Density Pipe** to RX Standard or NZS Standard
- Maximum working pressure 1200 kpa or 173 PSI
- UV stabilised to resist breakdown in sunlight.
- Suitable for municipal use and domestic supply.
- New Zealand manufactured by RX Plastics
- Robust strong fitting.
- All connection threads BSPT
- Fittings should be tightened with a wrench

## Tapping Saddles

- Body - Polypropylene
- Reinforcing ring, Nuts and bolts - Stainless steel
- Sealing ring - Nitrile rubber seal
- Suitable for use with **LOW and HIGH Density Pipe** manufactured to RX or NZ Standard and **MEDIUM Density MDID Pipe** as manufactured by RX Plastics Ltd or as specified
- Maximum working pressure 1200 kpa or 173 PSI
- Easy installation (2 or 4 bolts)
- Drill to "liven" connection.
- All connection threads female BSPT.
- No obstruction to flow
- Full flow external fit fitting

## Size



**RXC Coupler**  
15mm, 20mm, 25mm,  
32mm, 40mm, 50mm



**RXMC Male Coupler**  
15mm, 20mm, 25mm,  
32mm, 40mm, 50mm



**RXFC Female Coupler**  
15mm, 20mm, 25mm,  
32mm, 40mm, 50mm



**RXME Male Elbow**  
15mm, 20mm, 25mm



**RXT Tee**  
15mm, 20mm, 25mm,  
32mm, 40mm, 50mm



**RXFT Female Tee**  
15mm, 20mm, 25mm,  
32mm, 40mm, 50mm



**RXE Elbow**  
15mm, 20mm, 25mm,  
32mm, 40mm, 50mm



**RXFE Female Elbow**  
15mm, 20mm, 25mm,  
32mm, 40mm, 50mm



**RXTS-2 Tapping Saddle 2 Bolt**  
20x15mm, 20x20mm,  
25x15mm, 25x20mm,  
32x15mm, 32x20mm



**RXTS-4 Tapping Saddle 4 Bolt**  
40x15mm, 40x20mm,  
40x25mm, 40x32mm,  
50x15mm, 50x20mm,  
50x25mm, 50x32mm



**RXTB Tapping Saddle Back**  
20mm, 25mm, 32mm,  
40mm, 50mm

## Spare Parts Available



**SOR Compression O'Ring**  
15mm, 20mm, 25mm,  
32mm, 40mm, 50mm



**SCS Compression Sleeve**

**RXDTS-2  
Double Tapping Saddle 2  
Bolt**  
20x15mm, 20x20mm,  
25x15mm, 25x20mm,  
32x15mm, 32x20mm

**Compression Fittings  
suitable for:**  
HDPE 15 - 50mm  
MDID 15 - 50mm  
LDPE 15 - 40mm  
For pressure up to 174 psi  
(12.5 Bar)



**SCN Compression Nut**  
15mm, 20mm, 25mm,  
32mm, 40mm, 50mm

**RXDTS-4  
Double Tapping Saddle 4  
Bolt**  
40x15mm, 40x20mm,  
40x25mm, 40x32mm,  
50x15mm, 50x20mm,  
50x25mm, 50x32mm

**Tapping Saddles suitable  
for:**  
HDPE 15 - 50mm  
MDID 15 - 50mm  
LDPE 15 - 50mm  
For pressure up to 174 psi  
(12.5 Bar)



**SLR Compression Locking  
Ring**  
15mm, 20mm, 25mm,  
32mm, 40mm, 50mm